

10NW64

LF Drivers - 10.0 Inches



- 600 W continuous program power capacity
- 64 mm (2.5 in) copper voice coil
- 50 - 2500 Hz response
- 96 dB sensitivity
- Neodymium magnet allows a very light yet powerful motor assembly
- Shorting copper cap for extended HF response
- Ventilated voice coil gap for reduced power

Specifications

Nominal diameter	250 mm (10.0 in)
Nominal impedance	8 Ω
Minimum impedance	6.5 Ω
Nominal power handling ¹	300 W
Continuous power handling ²	600 W
Sensitivity (1W/1m) ³	96.0 dB
Frequency range	50 - 2500 Hz
Voice coil diameter	64 mm (2.5 in)
Winding material	Copper
Former material	Glass Fibre
Winding depth	16 mm (0.62 in)
Magnetic gap depth	8 mm (0.31 in)
Flux density	1.25 T

Design

Surround shape	Double Roll
Cone shape	Exponential
Magnet material	Neodymium Inside Slug

Design

Spider	Single
Pole design	Straight Pole
Woofer cone treatment	TWP Waterproof Both Sides
Recommended enclosure	26.0 dm ³ (0.92 ft ³)
Recommended tuning	53 Hz

Parameters⁴

Fs	50 Hz
Re	5.2 Ω
Qes	0.27
Qms	4.5
Qts	0.26
Vas	27.5 dm ³ (0.95 ft ³)
Sd	320.0 cm ² (50.0 in ²)
η_0	1.3 %
Xmax	8.0 mm
Xvar	10.0 mm
Mms	47 g
Bl	17.5 Txm

Parameters

Le	0.47 mH
EBP	185 Hz

Mounting And Shipping Info

Overall diameter	261 mm (10.3 in)
Bolt circle diameter	245 mm (9.6 in)
Baffle cutout diameter	230.0 mm (8.8 in)
Depth	113 mm (4.4 in)
Flange and gasket thickness	13 mm (0.5 in)
Air volume occupied by driver	1.5 dm ³ (0.05 ft ³)
Net weight	2.9 kg (6.4 lb)
Shipping units	1
Shipping weight	3.5 kg (7.7 lb)
Shipping box	330x330x160 mm (13x13x6.3 in)


Service Kit

RCK10NW648

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

Frequency Response (2,83 Vrms/1 m)



Model: **10 NW 64**
Enclosure Type: **Bass Reflex**

Internal Net Volume (Liters): **26**
Tuning Frequency (Hz): **53** Port Area (cm²): **69,4**
Frequency (-3 dB) (Hz): **53,4** Port Length (cm): **20,4**

Excursion Limited Maximum SPL at 1 meter (dB): **116,4** equal to **248,0** Watts (Bass Band Power Rating)
Thermal Limited Maximum SPL at 1 meter (dB): **117,3** equal to **300,0** Watts (Mid Band Power Rating)