

6^{1/2}" - SHIELDED PAPER CONE DRIVER - 170 mm**CLASSIC SERIES**


Shielded magnet for audio/video
 Extended bass response (Fs : 48 Hz)
 Paper cone
 Foam suspension
 Long excursion
 High temperature voice coil
 Stamped steel chassis

Anti-magnétique pour audio/vidéo
 Réponse étendue dans le grave (Fs : 48 Hz)
 Cône papier
 Suspension mousse
 Grande excursion
 Bobine haute température
 Châssis acier embouti



The low free air resonance and compact paper cone of this 6^{1/2}" bass midrange driver make it ideally suited for mini-enclosures. The high temperature 1" voice coil ensures good power handling. The magnet structure is fully shielded (compensation magnet + shield) for audio/video application. The "Suggested applications" charts indicate various driver loads, including the box alignment used to measure the response curve (Vb REF). The response curves shown on the diagram indicate the predicted low end response of the driver in the suggested box volume (Vb) with suggested port (Dp-Lp).


Ce haut-parleur très compact, 170 mm, combine une bande passante étendue à de réelles possibilités de longues excursions. La résonance basse pour sa taille le destine plus particulièrement à de petites enceintes, satellites triphonique, ... La bobine haute température sur support aluminium autorise une puissance admissible importante. Il est doté d'une contre-ferrite et d'un capot anti-magnétique (application audio/vidéo). Le tableau "Suggested applications" indique différents types de charge dont celui utilisé pour la mesure de la courbe de réponse (Vb REF). Les courbes publiées correspondent à la réponse dans le grave pour un volume (Vb) et une dimension d'évent donnée (Vp-Lp).



AT170M0 W08PMP2513



101192N

RESPONSE CURVE
refer to page 16



SPECIFICATIONS			
Technical Characteristics	Symbol	Value	Units
PRIMARY APPLICATION			
Nominal Impedance	Z	8	Ω
Resonance Frequency	Fs	48	Hz
Nominal Power Handling	P	50	W
Sensitivity	E	90	dB
VOICE COIL			
Voice coil diameter	Ø	25	mm
Minimum Impedance	Zmin	6,3	Ω
DC Resistance	Re	6,4	Ω
Voice Coil Inductance	Lbm	0,22	mH
Voice coil Length	h	11	mm
Former	-	Aluminium	-
Number of layers	n	2	-
MAGNET			
Magnet dimensions	Ø x h	(72x15)+16x10	mm
Magnet weight	m	0,34	kg
Flux density	B	1,1	T
Force factor	BL	4,32	NA ¹
Height of magnetic gap	He	4	mm
Stray flux	Fmag	3	Am ²
Linear excursion	Xmax	±3,5	mm
PARAMETERS			
Suspension Compliance	Cms	1,38.10 ⁻³	mN ⁻¹
Mechanical Q Factor	Qms	4,08	-
Electrical Q Factor	Qes	0,83	-
Total Q Factor	Qts	0,69	-
Mechanical Resistance	Rms	0,59	kg s ⁻¹
Moving Mass	Mms	8,1.10 ⁻⁵	kg
Effective Piston Area	S	1,4.10 ⁻²	m ²
Volume Equivalent of Air at Cas	Vas	36,2.10 ⁻³	m ³
Mass of speaker	M	0,8	kg

APPLICATION PARAMETERS		
Vb	Box volume	dm ³
Fb	Tuning frequency	Hz
Dp	Port diameter	cm
Lp	Port length	cm



Please refer to method of measurement and measurement conditions pages 15 to 19.
Audax may, without prior notification modify the specifications on its products further to research and development requirements.