





DE10 | HF Drivers

40 W continuous program power capacity
 1" horn throat diameter
 25 mm (1 in) aluminium voice coil
 Mylar diaphragm
 1500 – 18000 Hz response
 107 dB sensitivity



Specifications

Throat Diameter	25 mm (1 in)
Nominal Impedance	8 ohm
Minimum Impedance	6.3 ohm
Nominal Power Handling	20 W
Continuous Power Handling	40 W
Sensitivity (1W/1m)	107 dB
Frequency Range	1.5 -18 kHz
Recommended Crossover	2.5 kHz
Voice Coil Diameter	25 mm (1 in)
Winding Material	Aluminium
Inductance	0.1 mH
Diaphragm Material	Mylar
Flux Density	1.55 T

Mounting and Shipping Info

Two M5 holes 180° on 76 mm (3 in) diameter	
Overall Diameter	90 mm (3.5 in)
Depth	53 mm (2.1 in)
Net Weight (1 unit)	0.8 kg (1.8 lb)
Shipping Weight (8 units)	6.7 kg (14.7 lb)
Shipping Box (8 units)	220x220x150 mm (8.7x8.7x5.9 in)

Horns
 HF Drivers
 Coaxials
 LF Nd Drivers
 LF Drivers

