



DE620

HF Drivers - 1.4 Inches

- 160 W continuous program power capacity
- 1.4" horn throat diameter
- 65 mm (2.5 in) aluminium voice coil
- Titanium diaphragm
- 1000 – 18000 Hz response
- 107 dB sensitivity
- Neodymium magnet assembly with shorting copper cap

Specification

Throat Diameter	1.4 mm (36 in)
Nominal Impedance	8 ohm
Minimum Impedance	7.9 ohm
Nominal Power Handling (AES)	80 W
Continuous Power Handling	160 W
Sensitivity (1W/1m)	107 dB
Frequency Range	1 - 18 Hz
Recommended Crossover	1.2 kHz
Voice Coil Diameter	65 mm (2.5 in)
Winding Material	Aluminium
Inductance	0.15 mH
Diaphragm material	Titanium
Flux Density	1.8 T
Magnet Material	Neodymium Ring

Mounting & Shipping

Net Weight	1.75 kg (3.85 lb)
Shipping Weight	1.85 kg (4 lb)
Shipping Box	135x135x55 mm (5.3x5.3x2.1 in)

Replacement Diaphragm	MMD6208
-----------------------	---------

Mounting & Shipping

Overall Diameter	115 mm (4.5 in)
Depth	52 mm (2 in)